# QwikSeal®

by Fernco, Inc.

## If you can core through it, QwikSeal can connect to it.

| QwikSeal Advantages | | OTHERS |
|---|---|---|
| **Meets ASTM C 923** | ✔ | |
| When tested in Concrete Manholes: | ✔ | |
| - Creates a compression seal that is water tight up to 10 psi | ✔ | |
| - Can handle up to 7 degrees of deflection | ✔ | |
| Easy color identification - Grey = Sch 40, Green = SDR-35 | ✔ | |
| Not dependant on the host pipe size, type or material | ✔ | |
| Reduced complexity: 1 QwikSeal = Many Solutions | ✔ | |
| Less inventory = More turns | ✔ | |

| Part No. | Pipe Inlet | Pipe Size Application |
|---|---|---|
| QS-4 | 4" SDR-35 | 8" diameter and larger pipe |
| QS-4S40 | 4" SCH-40 | 8" diameter and larger pipe |
| QS-6 | 6" SDR-35 | 10" diameter and larger pipe |
| QS-6S40 | 6" SCH-40 | 10" diameter and larger pipe |
| QS-8 | 8" SDR-35 | 15" diameter and larger pipe |

Fernco Coring Bits and Hole Saws on back.

Fernco® Inc.

Environmental Commitment


**United States**
PH: 810-653-9626
FX: 810-653-8714

www.fernco.com

**Canada**
PH: 519-332-6711
FX: 519-332-8610

QwikSeal® by Fernco, Inc.

# *Save money with our **NEW** lower cost hole saws!*

## ***NEW*** Fernco Hole Saws

- General purpose tempered steel hole saw used for coring all types of plastic pipe materials
- Core through all thick walled plastic pipe including corrugated
- ***DO NOT*** use with steel, concrete or clay
- QS-ADAPTER adapts all hole saws to stationary and hand held drilling machines with 1¼" - 7 thread

| Part No. | Description |
|---|---|
| QS-5x6HS | 5" OD x 6" Deep Hole Saw with Arbor |
| QS-7x6HS | 7" OD x 6" Deep Hole Saw with Arbor |
| QS-9x6HS | 9" OD x 6" Deep Hole Saw with Arbor |
| QS-SAW5 | 5" OD x 6" Deep - HOLE SAW ONLY |
| QS-SAW7 | 7" OD x 6" Deep - HOLE SAW ONLY |
| QS-SAW9 | 9" OD x 6" Deep - HOLE SAW ONLY |
| QS-ARBOR | ⅜" x 12" Drill with ½" Arbor |
| QS-ADAPTER | 1¼" x ¾" Coring Machine Adapter |

## Fernco Coring Bits

- Diamond tipped abrasive bit used for coring reinforced and non-reinforced concrete and clay pipe materials
- Use with stationary drilling machines
- Use with water as coolant - ***DO NOT USE DRY***
- Adapts to 1¼" - 7 thread

| Part No. | Description |
|---|---|
| QS-5x14CB | 5" OD x 14" Length Abrasive Coring Bit |
| QS-7x14CB | 7" OD x 14" Length Abrasive Coring Bit |
| QS-9x14CB | 9" OD x 14" Length Abrasive Coring Bit |

Fernco® Inc.

**United States**
PH: 810-653-9626
FX: 810-653-8714

**www.fernco.com**

**Canada**
PH: 519-332-6711
FX: 519-332-8610