

HD Packer



HD Packer : Designed for entry into smaller pipe with excellent maneuverability. Special spring mounted, "Navigation Ball", to aid in passing through 45° and 90° elbows

Applications -

- Standard 3" through 6" Lateral PipePatch Installations
- Access through 3" Cleanouts in order to install 4" or 6" diameter PipePatch
- Can be used to install 3" to 4" and 4" to 6" Transitions

Additional info

- Removable eye-bolt pull cable connection installed in the packer's nose.
- A fixed pull cable connection is located at the tail.
- Undersized 1.65-inch diameter rubber nose and tail to allow for easy packer removal after patch installation.
- HD packers have no stiffening inner core, it may be necessary to add a few psi of pressure

Part Numbers & Specifications

- **FPP-PACK3-6-HD** (3-6 inch x 24 inch lateral repairs) Packer Dimensions: 1.80" OD x 39.5" Length
- **FPP-PACK3-6x48-HD** (3-6 inch x 48 inch lateral repairs) Packer Dimensions: 1.80" OD x 59" Length
- **FPP-PACK5-12-HD** (6-12 inch x 24 inch lateral repairs) Packer Dimensions: 4.18" OD x 59" Length
- **FPP-PACK5-12x48-HD** (6-12 inch x 48 inch lateral repairs) Packer Dimensions: 4.18" OD x 79" Length
- Maximum Inflation Pressure: 72 psi. (5 bar)

**Best to determine the appropriate pack-out pressure in an appropriate sized test pipe prior to patch installation. A minimum of 36 psi is recommended for each HD packer.*



Your 1 Source for Infrastructure
& Water Management Solutions

(877) 450-3701 • www.S1Eonline.com